



# UHF RFID Integrated Reader ID-IUR-3DBI-V2 (3 dBi, Compact)

Model ID-IUR-3DBI-V2 · Brand: Identium



A compact all-in-one UHF RFID reader with a built-in 3 dBi antenna for door frames, walls and counters. Reads EPC Gen2 tags at 1–3 m for doorway, checkout, file and access tracking.

## KEY FEATURES

- **Reader and 3 dBi antenna in one unit, with no coaxial cable to run or terminate**
- **Compact housing for wall or door-frame mounting**
- 1–3 m read range, tag dependent
- 860–960 MHz, EPC Gen2 / ISO 18000-6C
- Wiegand 26/34 or RS485 output with LED and buzzer prompt

## APPLICATIONS

Doorway item tracking

Warehouse doorway reads

Retail checkout lanes

Library book tracking

File and document tracking

Access and attendance

## SPECIFICATIONS

|            |                                               |
|------------|-----------------------------------------------|
| Model      | ID-IUR-3DBI-V2                                |
| Frequency  | 860–960 MHz (covers India's 865–868 MHz band) |
| Protocol   | EPC Gen2 / ISO 18000-6C                       |
| Antenna    | Integrated, 3 dBi                             |
| Read range | 1–3 m (tag dependent)                         |
| Interface  | Wiegand 26/34 or RS485                        |
| Mounting   | Wall or door frame                            |
| Indicator  | LED and buzzer                                |