



UHF RFID Integrated Reader ID-IUR-3DBI (3 dBi, Wiegand + RS485)

Model ID-IUR-3DBI · Brand: Identium



A compact wall-mount UHF RFID reader with a 3 dBi antenna built in and both Wiegand 26/34 and RS485 outputs. Reads UHF cards and tags at 1–3 m for indoor access control, attendance and checkpoints.

KEY FEATURES

- **Wiegand 26/34 and RS485 dual output for existing access and attendance panels**
- **Built-in 3 dBi antenna, 1–3 m read range (tag dependent)**
- 860–960 MHz, EPC Gen2 / ISO 18000-6C; covers India's 865–868 MHz band
- Compact wall-mount housing for indoor entry points and counters
- LED and buzzer confirm every read

APPLICATIONS

Employee access control

Time and attendance

Retail loss prevention

Inventory checkpoints

Conveyor checkpoints

Counter identification

SPECIFICATIONS

Model	ID-IUR-3DBI
Frequency	860–960 MHz (covers India's 865–868 MHz band)
Protocol	EPC Gen2 / ISO 18000-6C
Antenna	Built-in, 3 dBi
Read range	1–3 m (tag dependent)
Interface	Wiegand 26/34 and RS485 (dual)
Mounting	Wall mount, indoor
Indicator	LED and buzzer