



RFID Keyfob Tag RKT (LF, HF or UHF)

Model RKT · Brand: Identium



A 46 × 30 × 6 mm ABS keyfob for door access, attendance, gyms and parking, offered as LF 125 kHz EM4100, HF 13.56 MHz MIFARE Classic 1K or UHF EPC Gen2 to match the reader you already use.

KEY FEATURES

- **Three chip options: 125 kHz EM4100, MIFARE Classic 1K or UHF EPC Gen2**
- **46 × 30 × 6 mm oval ABS body with a 4 mm keyring hole**
- IP67 rated; works from –25 °C to +70 °C
- Read range: LF 2–10 cm, HF up to 10 cm, UHF 1–5 m
- Black, white, blue, red, yellow or green
- Logo engraving, colour printing and sequential numbering

APPLICATIONS

Office door access

Employee attendance

Gym and club membership

Car park barriers

School and college entry

Hotel and locker access

Loyalty programmes

SPECIFICATIONS

Frequency	125 kHz (LF), 13.56 MHz (HF) or 865 MHz band (UHF)
Chip	EM4100 (LF); MIFARE Classic 1K (HF)
Protocol	EPC Gen2 (UHF version)
Read range	LF 2–10 cm; HF up to 10 cm; UHF 1–5 m
Dimensions	46 × 30 × 6 mm (oval)
Material	ABS
IP rating	IP67
Operating temperature	–25 °C to +70 °C
Mounting	Keyring hole, 4 mm diameter
Colour	Black, white, blue, red, yellow, green
Printing	Logo engraving, colour printing, sequential serial numbers