



UHF On-Metal RFID Tag IDTS-2626 (26 × 26 mm, Screw Mount)

Model IDTS-2626 · Brand: Identium



A compact 26 × 26 mm UHF tag in a metal alloy and epoxy body that screws flush onto tools, brackets and machinery, rated from –40 °C to +200 °C for hot and cold assets.

KEY FEATURES

- **26 × 26 × 5.5 mm block for small metal surfaces**
- **Two 4.2 mm countersunk holes for flush screw fixing**
- Metal alloy body, PCB antenna and epoxy resin encapsulation
- Operating temperature –40 °C to +200 °C
- NXP UCODE 8, ISO 18000-6C, 128-bit EPC, 96-bit TID
- Approx. 2 m read range, depending on the reader

APPLICATIONS

Jigs and fixtures

Cylinder collars and valve guards

Moulds and dies

Machine sub-assemblies

Valves and pipeline flanges

Rolling-stock fittings

SPECIFICATIONS

Frequency	860–960 MHz (covers India's 865–868 MHz band)
Protocol	ISO 18000-6C
Chip	NXP UCODE 8
Memory	EPC 128 bits; TID 96 bits
Read range	Approx. 2 m (depends on reader)
Dimensions	26 × 26 × 5.5 mm
Material	Metal alloy, PCB and epoxy resin
Mounting	Two countersunk holes, 4.2 mm diameter
Colour	Black
Operating temperature	–40 °C to +200 °C