



UHF On-Metal RFID PCB Tag IDTS-6030 (60 × 30 mm)

Model IDTS-6030 · Brand: Identium



A 60 × 30 mm white PCB plate tag for metal assets, screwed or riveted in place and read at approx. 6 m on metal. It suits chassis faces, cabinet doors and equipment frames.

KEY FEATURES

- **60 × 30 × 4 mm rounded-corner plate sits flat on panels and frames**
- **Anti-metal design, approx. 6 m read range on metal**
- Two 4 mm end holes 54 mm apart, plus a central hole
- Operating temperature –20 °C to +150 °C
- U8 chip, ISO 18000-6C, 128-bit EPC, 96-bit TID

APPLICATIONS

Server and UPS chassis

Electrical cabinets

Cylinder cages

Steel racking bays

Stainless vessels

Depot equipment

SPECIFICATIONS

Frequency	860–960 MHz (covers India's 865–868 MHz band)
Protocol	ISO 18000-6C
Chip	U8
Memory	EPC 128 bits; TID 96 bits
Read range	Approx. 6 m on metal (depends on reader)
Dimensions	60 × 30 × 4 mm (4 mm at the highest point)
Material	PCB
Mounting	Two 4 mm holes at the ends, 54 mm apart, plus a central hole
Mounting surface	Metal (anti-metal design)
Shape	Rectangular plate with rounded corners
Colour	White
Operating temperature	–20 °C to +150 °C