



UHF On-Metal RFID Tag IDTS-7025 (70 × 25 mm, ABS)

Model IDTS-7025 · Brand: Identium



A slim 70 × 25 × 5 mm white ABS UHF tag that reads about 8 m on metal, with a screw hole at each end and adhesive backing, for rack uprights, control panels and cylinders.

KEY FEATURES

- **Approx. 8 m read range when mounted on metal**
- **Built-in dual-folded antenna designed for on-metal use**
- Slim 70 × 25 × 5 mm white ABS bar with rounded corners
- Two 4 mm screw holes plus peel-off double-sided adhesive
- NXP UCODE 9 (U9XE), ISO 18000-6C, 128-bit EPC, 96-bit TID
- Operating temperature –20 °C to +80 °C

APPLICATIONS

Rack uprights and beams

Server racks and switches

Control panels

Gas cylinder collars

Metal tool boxes

Roll cages and trolleys

SPECIFICATIONS

Frequency	860–960 MHz (covers India's 865–868 MHz band)
Protocol	ISO 18000-6C
Chip	NXP UCODE 9 (U9XE)
Memory	EPC 128 bits; TID 96 bits
Read range	Approx. 8 m on metal
Antenna	Built-in dual-folded design for on-metal use
Dimensions	70 × 25 × 5 mm
Material	ABS
Colour	White
Mounting	Two 4 mm holes (one at each end); peel-off double-sided adhesive
Operating temperature	–20 °C to +80 °C