



UHF RFID PCB Tag IDTS-7030 (70 × 30 mm, Four-Hole Mount)

Model IDTS-7030 · Brand: Identium



A thin 70 × 30 mm UHF PCB tag with four corner holes for bolting or riveting to plastic crates, pallets, carriers and other non-metal assets. It reads at approx. 6 m.

KEY FEATURES

- **Four 3.2 mm corner holes on 64 × 24 mm centres**
- **Thin 1.7 mm PCB plate, 70 × 30 mm with rounded corners**
- Approx. 6 m read range on non-metal surfaces
- Impinj Monza R6-P: 128-bit EPC, 96-bit TID, 32-bit user memory
- Operating temperature –20 °C to +150 °C
- Not an anti-metal tag: for plastic, wood and composites

APPLICATIONS

Plastic crates and totes

Plastic pallets

Warm process carriers

Composite panels

Polycarbonate enclosures

Plastic drums

SPECIFICATIONS

Frequency	860–960 MHz (covers India's 865–868 MHz band)
Protocol	ISO 18000-6C
Chip	Impinj Monza R6-P
Memory	EPC 128 bits; TID 96 bits; user 32 bits
Read range	Approx. 6 m (depends on reader)
Dimensions	70 × 30 × 1.7 mm
Material	PCB
Mounting	Four corner holes, 3.2 mm diameter, on 64 × 24 mm centres
Mounting surface	Non-metal surfaces only (not an anti-metal tag)
Shape	Rectangular plate with rounded corners
Colour	Black front; white / light grey back
Operating temperature	–20 °C to +150 °C